

Data sheet

Climatic Chamber KK 350 Smart PRO



The photo above is for reference only, may show additional options not included in standard equipment. The real appearance, particularly color and structure of the material may differ from the ones presented in the photo.

Advantages of the SMART PRO controller:

- large (7"), clear, full colour touch screen
- LAN, USB ports and WiFi for communication and data transfer
- multi-segment time and temperature programs
- overview of data in tabular and graphic form
- visual and sound alarm
- Admin function for management
- password protected log-in
 internal memory for programs and data storage
- event registry with user notifications
- LabDesk software and user manual for direct download




Smart PRO - preview screen





A. POLOK – KOWALSKA, S. KOWALSKI 44-300 WODZISŁAW ŚLĄSKI, UL. KOKOSZYCKA 172 C

air convection	forced
chamber capacity [l]	322
working capacity [l]	283
controller	microprocessor PID
display	7" full colour touch screen
TEMPERATURE AND HUMIDITY	
temperature range [°C]	0+60
temperature resolution every [°C]	0,1
temperature variation at 25°C and 60%rH [+/-°C]*	2,0
<u>'</u>	2,0 3090 (see chart for details)
temperature variation at 25°C and 60%rH [+/-°C]* relative humidity range [%] humidity resolution every [%]	· · · · · · · · · · · · · · · · · · ·
relative humidity range [%]	3090 (see chart for details)



tel. (+48) 32 453 91 70

obszar pracy krótkotrwałej (max.24 h) short-term work area (max. 24h)

Wilgotność względna / Relative humidity [%]

CHAMBER	
door	double (external solid, internal glass) / external glass (option)
interior	
Smart PRO	acid-proof stainless steel to DIN 1.4301
IG Smart PRO	acid-proof stainless steel to DIN 1.4301
housing	
Smart PRO	powder coated sheet
IG Smart PRO	stainless steel linen finish








overall dims [mm] /1/	
A width	660
B height	2000
depth C	990
internal dims [mm]	
width D	470
width D'	510
height E	1340
depth F	500
height I	1180

tel. (+48) 32 453 91 70



shelves (standard max) 3 11 max shelf workload [kg] /2/ 10 - reinforced shelf version (PW) [kg] /3/ 100 max unit workload [kg] 100 weight [kg] 125 ELECTRICAL PARAMETERS			
max shelf workload [kg] /2/ 10 - reinforced shelf version (PW) [kg] /3/ 100 max unit workload [kg] 100	ELECTRICAL PARAMETERS		
max shelf workload [kg] /2/ 10 - reinforced shelf version (PW) [kg] /3/ 100	weight [kg]	125	
max shelf workload [kg] /2/ 10	max unit workload [kg]	100	
	- reinforced shelf version (PW) [kg] /3/	100	
shelves (standard max) 3 11	max shelf workload [kg] /2/	10	
	shelves (standard max)	3 11	

ELECTRICAL I ARAPIETERS	
power supply	230V 50-60Hz
nominal power [W]	1850
refrigerant	R290 / GWP=3
warranty	24 months
manufacturer	POL-EKO-APARATURA

all the above technical data refer to standard units (without optional accessories)

- * variation (K) calculated for chamber as: K= +/- (T average max. T average min.) / 2
- ** other power supplies on request
- 1 depth doesn't include 50 mm of power cable
- 2 on uniformly loaded surface
- 3 reinforced shelf
- 4 reinforced version

OPTIONS AND ACCESSORIES



Order number: */A

Door with viewing window



Order number: */P INOX

Stainless steel wire shelf INOX



Order number: */PP

Perforated shelf







Order number: */PW Reinforced shelf



Order number: KUW GN*/* Stainless steel cuvettes



Order number: */FIT Phytotron system



Order number: FIT/R3 FIT panels independent control



Order number: GNZ Internal socket



Order number: KK/CP Low water level sensor



Order number: BRT/*/L or IQ/OQ/PQ Calibration and IQ, OQ, PQ qualification



Order number: BPP 12 Battery backup for display



Order number: PORT ALARM Dry alarm contact



Order number: USBK USB cable



LAN cable Order number: LANK



Order number: OCZ/20 Non-standard access port 20 mm



Order number: OCZ/30 Additional access port 30 mm



Order number: OCZ/60 Non-standard access port 60 mm



Order number: OCZ/100 Non-standard access port 100 mm



Order number: KK/Z Container for deionised water



Order number: KK/Z





tel. (+48) 32 453 91 70

e-mail: info@pol-eko.com.pl internet: www.pol-eko.com.pl

POL-EKO-APARATURA SP. J.

A. POLOK – KOWALSKA, S. KOWALSKI 44-300 WODZISŁAW ŚLĄSKI, UL. KOKOSZYCKA 172 C



Order number: CCTV

Camera inside the chamber



Order number: CCTV CAM

Additional camera







Want to know more?

If you have questions about this item, please give us a call on 01257 270 433.

Richmond Scientific are a family run business in Lancashire. We're a small team, and we're always just a phone call away. With over 30 years in the business there's not much we haven't seen before, and we're always happy to chat.

Have kit to sell?

Call us on 01257 270 433 Email: harry@richmondscientific.com

Visit: www.richmondscientific.com

Visit Website Sell used kit Our newsletter