

## Data Sheet

Mixing / Magnetic Stirrers



### RT 5 power IKAMAG®

The RT 5 power is a high-performance multi-position magnetic stirrer with 5 stirring positions and integrated temperature control plate. Precise temperature distribution on the heating plate makes it possible to perform series experiments.

- Simultaneously operating stirrers
- Absolute consistency over sample conditions for the individual samples

Accessories: IKAFLON® 15 Magnetic stirring bar, IKAFLON® 30 Magnetic stirring bar, IKAFLON® 10 Magnetic stirring bar, IKAFLON® 20 Magnetic stirring bar, H 11 Mains cable UK plug, H 11 Mains cable CH plug, RSE Stirring bar remover, IKAFLON® 25 Magnetic stirring bar, H 11 Mains cable Euro plug, H 11 Mains cable USA plug, TRIKA® 25 Magnetic stirring bar

#### Technical Data

Number of stirring positions	5
Stirring quantity max. per stirring position (H <sub>2</sub> O) [l]	0.4
Stirring position distance [mm]	90
Speed deviation of individual stirring positions [%]	5
Stirring quantity max. (H <sub>2</sub> O) [l]	2
Motor rating input [W]	7.2
Motor rating output [W]	1.8
Speed range [rpm]	0 - 1100
Stirring bar length max. [mm]	30
Heat output [W]	175
Heating temperature range [°C]	room temp. - 120
Temperature medium max. (dep. on vessel) [°C]	70
Heat control	scale 1-10
Speed control	scale 1-10
Temperature constancy in medium [±K]	2
Set-up plate material	silicone
Set-up plate dimensions [mm]	120 x 450
Dimensions (W x H x D) [mm]	138 x 65 x 552
Weight [kg]	3
Permissible ambient temperature [°C]	5 - 40
Permissible relative moisture [%]	80
Protection class according to DIN EN 60529	IP 42
RS 232 interface	no
Analog output	no
Voltage [V]	230 / 115 / 100
Frequency [Hz]	50/60
Power input [W]	185
<b>Ident. No.</b>	<b>2930300</b>