




The photo above is for reference only, may show additional options not included in standard equipment. The real appearance, particularly color and structure of the material may differ from the ones presented in the photo.

**Advantages of the SMART controller:**

- 4,3", clear, full colour touch screen
- LAN, USB ports for data transfer
- multi-segment time and temperature programs
- visual and sound alarm
- internal memory for programs and data storage
- event registry
- user manual for direct download
- Quick change of program parameters
- Alarm Bar
- operating with gloves on



**Smart** - preview screen

## TECHNICAL DATA

|                      |                               |
|----------------------|-------------------------------|
| air convection       | forced                        |
| chamber capacity [l] | 70 / 70 / 70                  |
| working capacity [l] | 55 / 55 / 55                  |
| controller           | microprocessor PID            |
| display              | 4,3" full colour touch screen |

## TEMPERATURE

|  |   |
|--|---|
| temperature range [°C]                 | 0...+15                                     |
| temperature resolution every ... [°C]  | 0,1   |
| temperature fluctuation at 4°C [±/°C]* | 0,4   |
| temperature variation at 4°C [±/°C]*   | 0,7   |
| temperature protection                 | class 1.0 to DIN 12880 / class 3.2 (option) |

## CHAMBER


|                 |  |
|-----------------|--|
| door type       | solid / glass or double (option) /4/     |
| <b>interior</b> |  |
| B Smart         | aluminium                                |
| C Smart         | stainless steel to DIN 1.4016            |
| CS Smart        | stainless steel to DIN 1.4016            |
| P Smart         | acid-proof stainless steel to DIN 1.4301 |
| PS Smart        | acid-proof stainless steel to DIN 1.4301 |
| <b>housing</b>  |  |
| B Smart         | powder coated sheet                      |
| C Smart         | powder coated sheet                      |
| CS Smart        | stainless steel polished                 |
| P Smart         | powder coated sheet                      |
| PS Smart        | stainless steel polished                 |

### overall dims [mm] /1/

|          |      |
|----------|------|
| width A  | 550  |
| height B | 1920 |
| depth C  | 680  |

### internal dims [mm]

|          |     |
|----------|-----|
| width D  | 430 |
| width D' | 470 |
| height E | 430 |
| depth F  | 300 |
| depth F' | 360 |



|                             |                       |
|-----------------------------|-----------------------|
| shelves (standard   max)    | 2   2 / 2   2 / 2   2 |
| max shelf workload [kg] /2/ | 10                    |
| max unit workload [kg]      | 20 / 20 / 20          |
| weight [kg]                 | 98                    |

## ELECTRICAL PARAMETERS

|                   |                 |
|-------------------|-----------------|
| voltage**         | 230V 50-60Hz    |
| nominal power [W] | 750             |
| refrigerant       | R1234ze / GWP=1 |
| warranty          | 24 months       |
| manufacturer      | POL-EKO         |

all the above technical data refer to standard units (without optional accessories)

\* - fluctuation measured in centre of the chamber; in space, variation (K) calculated for chamber as:

$K = \pm (T \text{ average max.} - T \text{ average min.}) / 2$

\*\* - other power supplies on request

1 - depth doesn't include 50 mm of power cable, the width does not include the 20 mm of rubber plug

2 - on uniformly loaded surface

3 - reinforced shelf


4 - additional internal glass door

## OPTIONS AND ACCESSORIES




Order number: \*/C

Internal glass door



Order number: \*/A

External glass door



Order number: \*/P


Wire shelf



**INOX**


Order number: \*/P INOX

Stainless steel wire shelf INOX




Order number: \*/PP

Perforated shelf




Order number: \*/PW

Reinforced shelf



Order number: KUW GN\*/\*


Stainless steel cuvettes



**ALU**

Order number: ST/CHL/SWP ALU

Aluminum drawer with powder coated slides



**INOX**

Order number: ST/CHL/SWP INOX

Stainless steel drawer with powder coated slides



**INOX/INOX**


Order number: ST/CHL/SWPN INOX

Stainless steel drawer with stainless steel slides



Order number: \*PLUS

Automatic defrosting function




Order number: GNZ

Internal socket



Order number: LabDesk

LabDesk software



Order number: BRT/\*L or IQ/OQ/PQ

Calibration and IQ, OQ, PQ qualification



Order number: \*/3.2

Over temperature protection 3.2 class according to DIN 12880



Order number: BPP 12

Battery backup for display




Order number: PORT ALARM

Dry alarm contact




Order number: LANK

LAN cable




Order number: OCZ/20

Non-standard access port 20 mm




Order number: OCZ/30

Additional access port 30 mm




Order number: OCZ/60

Non-standard access port 60 mm



Order number: OCZ/100

Non-standard access port 100 mm



Order number: KD

Access control