Richmond Scientific

Data sheet

print date: 2026-11-06

Drying Oven

SLW 115 Smart





The photo above is for reference only, may show additional options not included in standard equipment. The real appearance, particularly color and structure of the material may differ from the ones presented in the photo.

Advantages of the SMART controller:
- 4,3”, clear, full colour touch screen
- LAN, USB ports for data transfer
- multi-segment time and temperature programs
- visual and sound alarm
- internal memory for programs and data storage
- event registry
- user manual for direct download
- Quick change of program parameters
- Alarm Bar
- operating with gloves on



Smart - preview screen

TECHNICAL DATA

air convection	forced
chamber capacity [l]	151
working capacity [l]	107
controller	microprocessor PID
display	4,3" full colour touch screen


TEMPERATURE

temperature range [°C]	5°C above ambient temperature ... +300°C
temperature resolution every ... [°C]	0,1
temperature fluctuation at 105°C [+/-°C]*	0,2
temperature variation at 105°C [+/-°C]*	2
temperature protection	class 2.0 to DIN 12880 / class 3.1 (option)

CHAMBER

door type	solid / door with viewing window (option)
interior	
Smart	corrosion-resistant stainless steel to DIN 1.4301
IG Smart	corrosion-resistant stainless steel to DIN 1.4301
housing	
Smart	powder coated sheet
IG Smart	stainless steel linen finish

overall dims [mm] /1/	
width A	660
height B	850
depth C	720
internal dims [mm]	
width D	460
height E	540
depth F	440








shelves (standard | max)	2 | 7
max shelf workload [kg] /2/	25
- reinforced shelf version (PW) [kg] /3/	50
max unit workload [kg]	60
- reinforced unit version (W) [kg] /4/	120
weight [kg]	65

ELECTRICAL PARAMETERS	
voltage	230V 50/60Hz
nominal power [W]	2500
warranty	24 months
manufacturer	POL-EKO®

all the above technical data refer to standard units (without optional accessories)
* - fluctuation measured in centre of the chamber; in space, variation (K) calculated for chamber as:
K= +/- (T average max. - T average min.) / 2
** - other power supplies on request
1 - depth doesn't include 50 mm of power cable
2 - on uniformly loaded surface
3 - reinforced shelf
4 - reinforced version

OPTIONS AND ACCESSORIES

	Order number: */A	door with viewing window
	Order number: */P INOX	Stainless steel wire shelf INOX
	Order number: */PP	Perforated shelf
	Order number: */PW	Reinforced shelf
	Order number: KUW GN*/*	Stainless steel cuvettes
	Order number: QLK*	Castors
	Order number: */S or */S INOX	Table with castors
	Order number: */ST or */S INOX	Base on castors
	Order number: */W	Reinforced version
	Order number: OWW/OWW LED	Interior lighting
	Order number: HEPA	HEPA Clean Air Filter

LAB DESK	Order number: LabDesk	LabDesk software
>O<	Order number: BRT/*/L or IQ/OQ/PQ	Calibration and IQ, OQ, PQ qualification
DIN 3.1	Order number: */3.1	Over temperature protection 3.1 class according to DIN 12880
	Order number: RFID LOCK (SMART)	RFID LOCK (SMART)
	Order number: BPP 12	Battery backup for display
ALARM	Order number: PORT ALARM	Dry alarm contact
LAN	Order number: LANK	LAN cable
20mm	Order number: OCZ/20	Non-standard access port 20 mm
	Order number: OCZ/30	Additional access port 30 mm
	Order number: OCZ/60	Non-standard access port 60 mm
	Order number: OCZ/100	Non-standard access port 100 mm